



F3 CO 05

COLUMN LIFTS

LOAD CAPACITY: 500 KG



DESCRIPTION

This full aluminum frame column lift has been designed for utility and light commercial vehicles with flatbed or dropsided bodywork. With a lifting capacity of 500 kgs, the lift with folded platform provides a facility to load the rear of the vehicle over the lowered platform without having to unfold the platform, reducing the possibility of damaging the platform. It also has a much reduced drag effect on dropsided vehicles when travelling, due to the folded platform, and gives the vehicle better fuel economy than with a full depth platform.

VERY LIGHT FULL ALLUMINUM FRAME

F3CO 05 - min. body width = 1460 mm

SPECIFICATIONS

Platform depth:	F3 CO 05 S - 640+540 folded F3 CO 05 - 880 to 1480 mm
Platform width:	related to width over columns
Lift cylinders:	1
Tilt cylinders:	none
Autotilt at ground:	none - level ride
Platform opening:	Manual opening
Power supply:	12 or 24 V
Frame color:	full alluminum frame
Weight:	from 120 Kg

SUGGESTED OPTIONS

- Inside body remote control;
- Radio remote control;
- Top columns stiffeners for open body





F3 CO 05

COLUMN LIFTS

LOAD CAPACITY: 500 KG

TECHNICAL DATA

Mod.	Load capacity (load centre of gravity at 600 mm)	Width over columns* (W)	Width between columns	Column center	Platform depth (std. platform)	E (max)	Weight Kg
F3 CO 05	500 Kg	2284	2148	2216	900	1160	130
		2134	1998	2066	900	1050	125
		2084	1948	2016	900	950	120

*Width over columns minimum 1934 mm (on demand)

Centre of gravity of the vehicle depending on the platform depth and the type of the installations on the vehicle (see assembly instructions). The above mentioned weights are approximate and may vary according to production. Anteo reserves the right to change weights and technical specifications without prior notice. No indemnity for damages can be claimed from Anteo for changes in technical specifications and/or in weight.

Special F3 CO 05 Column lift to suit Barn Doors and Fridge Bodies



F3 CO 05 S – with folded platform

