



F3 RE 17 CC
F3 RE 22 CC
F3 RE 30 CC

RETRACTABLE TAIL-LIFTS
WITH CHROMIUM PLATED STEEL GUIDES

LOAD CAPACITY: 1700, 2200, 3000 KG



DESCRIPTION

F3 RE 17/22/30 CC with Chromed Guides, premium quality, perfect alignment, low maintenance for demanding applications in the regular transport business, such as supermarket and food distribution. The F3 RE 17/22 CC are extremely versatile lifts suitable for commercial trucks above 7.5T GVW, rigids, trailers and semi-trailers. The F3 RE 30 CC is the heavy duty retractable lift and is the perfect retractable lift to use in combination of heavy electric pallet jack. Retraction system with chromed guides, smooth hydraulic automatic tilt, high stiffness ideal to equip vehicles for customers that like high performances with lower maintenance costs.

SPECIFICATIONS

Platform:	Aluminium
Platform depth:	from 1300 to 2000 mm rear bumper EEC type approved
Lift cylinders:	2
Tilt cylinders:	2
Autotilt at ground:	hydraulic (with memory feature)
Sliding system:	Chromed steel guides with push-pull cylinder
Power supply:	12 or 24 V
Low maint. bushes:	greasable
Frame color:	Black KTL plus and powder paint
Weight:	from 545 Kg

SUGGESTED OPTIONS

- Inside body remote control;
- Radio remote control;
- Foot operated controls on platform;
- Blinking lights on platform;
- Roll stop;
- Torsion bar





F3 RE 17 CC
F3 RE 22 CC
F3 RE 30 CC

RETRACTABLE TAIL-LIFTS
WITH CHROMIUM PLATED STEEL GUIDES

LOAD CAPACITY: 1700, 2200, 3000 KG

TECHNICAL DATA

					RIGID		SEMI-TRAILER	
	Mod.	Load capacity (centre of gravity at 600 mm)	Floor to ground (max)	Platform Depth* (example)	Mounting space (min)	Weight* Kg	Mounting space (min)	Weight* Kg
01/2021 1 FOLD PLATFORM	F3 RE 17 H CC	1700 Kg	1290	1633 (600+1033)	1675	605	1690	605
	F3 RE 17 HS CC		1530	1783 (750+1033)	1985	645	2000	645
	F3 RE 17 HSS CC		1670	1983 (750+1233)	2080	695	2095	695
	F3 RE 22 H CC	2200 Kg	1290	1633 (600+1033)	1675	625	1690	625
	F3 RE 22 HS CC		1530	1783 (750+1033)	1985	665	2000	665
	F3 RE 22 HSS CC		1670	1983 (750+1233)	2080	715	2095	715
	F3 RE 30 H CC	3000 Kg	1290	1591 (558+1033)	1730	850	1730	850
	F3 RE 30 H1 CC		1370	1991 (758+1233)	1985	910	1985	910
	F3 RE 30 HS CC		1590	2041 (1008+1033)	2370	980	2370	980
2 FOLDS PLATFORM	F3 RE 17 H CC	1700 Kg	1290	1283 (700+583)	1165	545	1166	545
	F3 RE 17 HS CC		1530	1583 (850+733)	1315	610	1320	610
	F3 RE 17 HSS CC		1670	1783 (950+833)	1410	660	1422	660
	F3 RE 22 H CC	2200 Kg	1290	1283 (700+583)	1165	565	1166	565
	F3 RE 22 HS CC		1530	1583 (850+733)	1315	630	1320	630
	F3 RE 22 HSS CC		1670	1783 (950+833)	1410	660	1422	660

* Approximate weight for tail-lift equipped with aluminium platform 2450 mm wide.

The above mentioned weights are approximate and may vary according to production. Anteo reserves the right to change weights and technical specifications without prior notice. No indemnity for damages can be claimed from Anteo for changes in technical specifications and/or in weight.



**LOW MAINTENANCE BUSHES
AND CHROMIUM PLATED PINS.**



**POWDER COATING PAINT (2)
ADDED TO KTL PLUS (1). NO
RUST AND NO SALT STAINS.**



**HI-TENSILE ALUMINUM
SPECIALISTS SINCE 1992.**



**LOW NOISE POWER UNIT
& NO ELECTRONICS = EASY
MAINTENANCE**